

www.tapespec.co.nz



www.acme.co.nz

SELF ADHESIVE LOPES

PRODUCT DATA SHEET

0191, 0192, 0193, 0194, 0195 SELF ADHESIVE LOPES

DESCRIPTION

The self adhesive lopes are made from strong clear plastic film and are coated on one side with a high tack adhesive system. The adhesive is covered with a easy release white silicone release paper, allowing for accurate placement of the lope onto cartons, bubble wrap etc. All lopes have a side opening for ease of document placement.

LABELOPE TYPES



0191 "DOCUMENTS ENCLOSED"



0192 "PACKING SLIP ENCLOSED"



0193 "INVOICE ENCLOSED"



0194 PLAIN (NO MESSAGE)



0195 SPECIAL PRINT REQUIREMENT

FEATURES



CONFORMABLE

The lopes are conformable on uneven surfaces.



EASY USE SIDE OPENING

All lopes have a side opening for ease of document placement before closure.



SECURE, WATERPROOF PROTECTION

Secure & waterproof protection of documents, invoices & packing slips.

TYPICAL APPLICATIONS

- Used for the protection of documents, invoices, packing lists, components and promotions.
- Allows inspection of the delivery without opening goods.
- Ensures documents arrive with goods no need to wait for separate delivery of invoices or packing slips.



EASY IDENTIFICATION

Makes documents easily visible & quick to identify. Allows for fast inspection of goods on arrival without opening the package.

- Removes the need for additional labelling address can be shown.
- Makes documents easily visible and is quick / simple to use.
- Excellent for track and trace information.

TECHNICAL INFORMATION

Size	142 mm x 115 mm
Quantity	1000 per box 4 Boxes per carton
Service Temperature	-18°C to 60°C
Storage Temperature	12°C to 25°C
Code	0192 - "Packing Slip Enclosed" 0193 - "Invoice Enclosed" 0194 - Plain 0195 - Special Print Requirement
Number of lopes per box	1000 lopes
Lope boxes per carton	4

Slit to various width sizes as required.

NOTE: We recommend tape product testing to assess the suitability of the selected product to the end application & conditions. For surface preparation and guidelines please refer to our website www.tapespec.co.nz_Advanced Tape Application Guide.

SURFACE SUBSTRATE CONDITION & PREPARATION

The surfaces to be bonded must be dry & free from any contamination including dust, oils, & fats, oxidisation, release agents & any other known contamination.

The correct choice of surface cleaner depends on the surface properties. Essentially nongreasy cleaners are recommended including isopropanol alcohol (mixed 50/50 with clean water). Cleaning cloths must be clean, grease & fat free with no loose fibers or cloth particles.

The bond strength is dependent upon the contact pressure of the adhesive to substrate. To assist this process all adhesive tapes require firm hand or roller pressure.

BONDING APPLICATION TEMPERATURE

We recommend that the product, substrate & environment should be between +15°C & +25°C. Ensure that the adhesive product & substrates are allowed time to adjust to the environment temperature before bonding. For product storage we recommend that products are stored in their original packaging under dry conditions, ideally at room temperature but not warmer than +25°C. High relative humidity & direct sunlight must be avoided at all costs.

For more detailed handling instructions please refer to our comprehensive application guide.

PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose, prior to use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information please refer to our detailed Surface Condition & Preparation Guide.



www.acme.co.nz

PH: 0800 226 369

