

## DESCRIPTION

Lupin Exterior Masking Tape is an unique product made from an extremely strong Woven Plastic Backing Film coated with an extra high tack Premium Acrylic Adhesive. Designed for heavy duty outdoor use & rough environments. Outperforms other exterior vinyl & cloth masking tapes, with longer life & no residue clean removal. Made by one of the worlds leading masking tape manufactures in Japan.



<b>ADHESION LEVEL</b>	Extra High
<b>SURFACE TYPE</b>	Rough to Extreme Texture

## FEATURES



### CLEAR IDENTIFICATION

Highly visible pink colour for clear identification of the masking area.




### EXTREME STRENGTH

Extremely strong Woven Plastic Backing Film coated with extra high tack Premium Acrylic Adhesive.



### EXTREME CONDITIONS

Very good UV, weather & age resistance. Designed for heavy duty outdoor use in extreme environments, outperforming other exterior vinyl & cloth masking tapes.



### EXTREME SURFACES

Suitable for most surfaces types: concrete, tiles, composite panels, plastics, aluminum & metals, without any adhesive leaching / shadowing effects.



### 30 DAYS + CLEAN REMOVAL

Tested up to 30+ days clean removal - leaves no stain & residue on most surfaces.



### EASY HAND TEARABLE

Easily hand tearable for ease of use.

## TYPICAL APPLICATIONS

- Exterior fine line masking applications.
- Various sandblasting & marine masking applications.
- Sharp finish line masking on Elastomeric Paint & Membrane systems.
- Excellent for the application of masking film onto surfaces such as eaves & soffits for secure holding power with clean removal.
- Often used for masking & protection during plastering / stucco application where a heavy duty exterior tape is required.
- Suitable for most surface types: concrete, tiles, composite panels, plastics, aluminum & metals. Prior surface testing is recommended to assess tape suitability to the surface & application.

## TECHNICAL INFORMATION

Backing	Woven Plastic
Adhesive	Premium Acrylic
Colour	Pink
Thickness	0.16 mm
Adhesive Strength	3.84 N/10mm
Tensile Strength	36.9N/15mm
Elongation	6.6 %
Temperature Resistance	+60°C
Shelf Life	12 months when stored in cartons at 23°C & 65% relative humidity
Solvent Resistance	Good
Age Resistance	Good
Core Size	76mm
Roll Length	25m
Standard Roll Width	18 / 24 / 36 / 48mm

\* Available to slit to any width size up to 1210mm.

## SIMILAR PRODUCTS

- No 11. Soft PVC Masking Tape
- No 10. Premium Cloth Masking Tape

## SURFACE SUBSTRATE CONDITION & PREPARATION

The surfaces to be bonded must be dry & free from any contamination including dust, oils, & fats, oxidisation, release agents & any other known contamination.

The correct choice of surface cleaner depends on the surface properties. Essentially non-greasy cleaners are recommended including isopropanol alcohol (mixed 50/50 with clean water) & acetone. Cleaning cloths must be clean, grease & fat free with no loose fibers or cloth particles.

The bond strength is dependent upon the contact pressure of the adhesive to substrate. To assist this process all adhesive tapes require firm hand or roller pressure.

## BONDING APPLICATION TEMPERATURE

We recommend that the product, substrate & environment should be between +15°C & 30°C. Ensure that the adhesive product & substrates are allowed time to adjust to the environment temperature before bonding.

For product storage we recommend that products are stored in their original packaging under dry conditions, ideally at room temperature but not warmer than +30°C. High relative humidity & direct sunlight must be avoided at all costs.

For more detailed handling instructions please refer to our comprehensive application guide.

## PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose, prior to use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information please refer to our detailed Surface Condition & Preparation Guide.

tapespec.co.nz 0800 367 8273

100% NZ owned & operated since 1998 New Zealand Tape Specialists Ltd

**tape**spec™  
● ● ● ●  
STICK WITH QUALITY