

# PRODUCT DATA SHEET

**AS891**  
PREMIUM  
MASKING TAPE - CREPE

## DESCRIPTION

The AS891 is a premium Decorative Automotive & Industrial masking tape, made from smooth strong crepe paper backing and coated with a high quality solvent rubber adhesive system. The crepe paper is clearly identified by a bright yellow colour. Available in both retail labeled and bulk package forms.



<b>ADHESION LEVEL</b>	MEDIUM / HIGH
<b>SURFACE TYPE</b>	MULTI-SURFACE

## FEATURES



**STRONG CREPE PAPER BACKING**

Made from a smooth, strong crepe paper backing with excellent rip resistance and good waterproof properties. Excellent tape to tape / double masking ability.



**SOLVENT NATURAL RUBBER**

Premium Solvent Natural Rubber provides good conformability to irregular surfaces & leaves no residue on most surfaces when removed. Resistance to most paint solvents & thinners – prior testing recommended.



**CLEAN FINISH LINE**

Provides painters with clean finish lines & very good conformability & resistance to paint bleed. Excellent for multi purpose decorative paint masking tape.



**MULTI SURFACE**

Suitable for most surface types without any adhesive leaching or shadowing effects. Surface types: wood, metal, plastic, glass, laminates & rubber.



**GOOD TEMPERATURE RESISTANCE**

Very good temperature resistance - up to +130°C for short period.



**INTERIOR USE**

Excellent for interior use, with limited exterior exposure (test to 2 days).

## TYPICAL APPLICATIONS

- Used as a premium Decorative Automotive / Industrial Masking tape.
- Used in Automotive (car & truck) repair & professional paint body shops.
- Excellent as a multi-purpose Decorative / Industrial paint masking tape.
- Suitable for various splicing, tabbing & general holding applications.
- Used for colour coding, marking & sealing applications.
- Surfaces Types: Wood, metal, plastic, glass, laminates, & rubber.

## ADVANTAGES

### QUICK & EASY TO USE

Hand tearable for ease of use.  
Easy off the roll.

### SLIT TO SIZE IN NZ

Roll widths are slit to required sizes in New Zealand.  
Fast delivery to site throughout New Zealand.

### FREE TECHNICAL ADVICE

Free technical assistance, samples and advice  
available throughout NZ from the tape spec  
sales team.



## TAPE STRUCTURE



Crepe Paper

Premium Solvent Natural  
Rubber Adhesive



## PRODUCT

**PROFESSIONAL PAINTERS  
MASKING TAPE - CREPE**

Available thickness: **0.15MM**

## IMPORTANT

Used only on tested & approved surfaces to ensure tape is selected correctly for the application & conditions. Ensure that all surface manufacturers recommendations are followed.

All surfaces must be correctly sealed &/ or primed & only apply tape to clean, dry, non-flaky surfaces. Also test the tape in an inconspicuous place prior to use, especially on delicate or older worn surfaces.

Liability limited to tape replacement.

## TECHNICAL INFORMATION

Backing	Crepe Paper
Adhesive	Natural Solvent Rubber Resin
Colour	Yellow
Tape thickness	0.15 mm
Elongation at break	10+ (%)
Adhesion to steel	2.98 N/cm (PSTC 101)
Tensile Strength	31.4 N/cm (PSTC 131)
Water Repellent	30 mins - Beaded
Shelf life	12 months from manufacture date (correct storage).
Temperature Range	-10°C to +95°C (up to 130°C for approx. 30 mins)
Storage Temperature	12°C to 25°C (out of sunlight)
Core Size	76mm
Roll Length	50m
Standard Roll Width	18, 24, 36 & 48mm
<i>Rolls can be slit to required width sizes from our master log roll at 1200mm wide.</i>	

Slit to various width sizes as required.

## SIMILAR PRODUCTS

- AS817 Multi-Purpose Yellow Crepe Paper
- No 8 Professional Grade Masking Tape

## SURFACE SUBSTRATE CONDITION & PREPARATION

The surface on which the tape is to be used must be clean, dry and free from grease and dust.

Remember that the pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels.

The recommended application temperature is between 12°C and 25°C.

## PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose, prior to use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information please refer to our detailed Surface Condition & Preparation Guide.

NOTE: We recommend tape product testing to assess the suitability of the selected product to the end application & conditions. For surface preparation and guidelines please refer to our website [www.tapespec.co.nz](http://www.tapespec.co.nz) Advanced Tape Application Guide.

[www.tapespec.co.nz](http://www.tapespec.co.nz)

0800 226 369

New Zealand Tape Specialists - Acme Supplies Limited ([www.acme.co.nz](http://www.acme.co.nz))

**tape**spec™  
● ● ● ●  
NEW ZEALAND TAPE SPECIALISTS