

## DESCRIPTION

The **Labelopes** are made from strong clear plastic film and are coated on one side with a high tack adhesive system. The adhesive is covered with an easy release white silicone paper, allowing for accurate placement of the lope onto cartons, bubblewrap etc. All lopes have a side opening for ease of document placement.



## FEATURES



### CLEAR PLASTIC FILM

Made from strong clear plastic film - makes documents easily visible, quick to identify & waterproof protection. Allows inspection of the delivery without opening goods.



### CONFORMABLE

All lopes are coated on one side with a high tack adhesive system that is conformable on uneven surfaces.



### SECURE DOCUMENTS

All lopes have a side opening for ease of document placement before secure seal it.



### EASY RELEASE LINER

With an easy release white silicone paper, allowing for accurate placement of the lope onto cartons, bubble-wrap etc.

## LABELOPE TYPES



**0192**

"Packing Slip Enclosed"



**0198-Z2**

"Packing Slip Enclosed"  
*Extra High Tack*



**0193**

"Invoice Enclosed"



**0194**

Plain



**0195**

Special Custom Print  
*With Your Own Branding*

## TYPICAL APPLICATIONS

- Used for the protection of documents, invoices, packing lists, components and promotions.
- Allows inspection of the delivery without opening goods.
- Ensures documents arrive with goods - no need to wait for separate delivery of invoices or packing slips.
- Removes the need for additional labeling - address can be shown.
- Excellent for track and trace information.

## TECHNICAL INFORMATION

Release Liner	White Silicone Paper
Adhesive	High Tack Adhesive System
Adhesive Strength	High Tack
Service Temperature	-18°C to +60°C
Storage Temperature	12°C to +25°C
Colour <i>(Background - Writing)</i>	0192 - (Yellow - Black) 0193- (Yellow - Black) 0194 - (Clear) 0195 - (Special Custom Print*) 0198-Z2 - (Orange - Black)
Size	150mm x 115mm <i>Larger size lopes also available upon request</i>
Quantity / Box	1000 lopes

\* Special Custom Print - a customized print on labelopes with your own branding / logo / message. Available to print multi colours. Please contact us for more information.

## SURFACE SUBSTRATE CONDITION & PREPARATION

The surfaces to be bonded must be dry & free from any contamination including dust, oils, & fats, oxidisation, release agents & any other known contamination.

The correct choice of surface cleaner depends on the surface properties. Essentially non-greasy cleaners are recommended including isopropanol alcohol (mixed 50/50 with clean water) & acetone. Cleaning cloths must be clean, grease & fat free with no loose fibers or cloth particles.

The bond strength is dependent upon the contact pressure of the adhesive to substrate. To assist this process all adhesive tapes require firm hand or roller pressure.

## BONDING APPLICATION TEMPERATURE

We recommend that the product, substrate & environment should be between +15°C & 30°C. Ensure that the adhesive product & substrates are allowed time to adjust to the environment temperature before bonding.

For product storage we recommend that products are stored in their original packaging under dry conditions, ideally at room temperature but not warmer than +30°C. High relative humidity & direct sunlight must be avoided at all costs.

For more detailed handling instructions please refer to our comprehensive application guide.

## PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose, prior to use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information please refer to our detailed Surface Condition & Preparation Guide.

**tapespec.co.nz 0800 367 8273**

100% NZ owned & operated since 1998 New Zealand Tape Specialists Ltd

**tape**spec™  
● ● ● ●  
STICK WITH QUALITY