

Anti Slip & Safety Tapes selected for the New Zealand marketplace

An extensive range of anti slip grip tapes designed to help companies meet Health & Safety regulations. These products can be applied to most surfaces and are ideal for demanding applications to prevent slips, falls & accidents.

For use at home, office, schools, factories, hospitals, warehouses and marine applications. Both grades are suitable for indoor & outdoor use.

Code: 4600 Coarse/Heavy **Duty Grit Grade** Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters Retail code: 4600R Labeled 50 mm x 5 meters. Code: 4700 Medium Grit Grade Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters

Code: 4601 Coarse/Heavy **Duty Grit Grade** Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters

Code: 4704 Medium Grit Grade Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters



Black & Yellow

Code: 4702 Medium Grit Grade Standard Roll Sizes: 25, 50,

100 & 150 mm x 18.3 meters

Code: 4703 Medium Grit Grade

Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters

Transparent

Code: **4701** Medium Grit Grade

Standard Roll Sizes: 25, 50, 100 & 150 mm x 18.3 meters

BROUGHT TO YOU BY





Floor Marking

0008

Heavy duty PVC film with an aggressive rubber adhesive.

Excellent for factory & warehouse demarcation identification.

Aggressive pressure sensitive rubber adhesive with good long life bonding power & resistant to most cleaning agents.

Extra tough plasticized PVC film for extreme environments.

Extensive colour choice for coding & marking purposes.

Widths: Slit to customer requirements. max:1280 mm Colours: Red, Black, Yellow, White, Blue & (Green 33m) Roll Length: 30m

Safety / Hazard Tape 0009

Heavy duty PVC film coated with an aggressive rubber adhesive.

Excellent for factory & warehouse safety / hazard identification.

Aggressive pressure sensitive rubber adhesive with good long life bonding power & resistant to most cleaning agents. Extra tough plasticized PVC film for extreme environments.

Extensive colour combinations for highlighting danger, hazard & safety areas.

Identification of fire fighting equipment, first aids points, assembly areas, fulfills health & safety requirements.

Widths: Slit to customer requirements. max:1280 mm Colours: Yellow & Black, Red & White, Green & White Roll Length: 33m

Cloth Hazard Tape 0011

Premium Cloth Tape coated with an aggressive rubber adhesive. Used as a premium hazard warning indicator tape for construction sites, warehouse areas. factories, schools & transport facilities. . The cloth backing provides excellent waterproofing, with good flexibility & conformability. Aggressive rubber adhesive bonds securely to most surfaces (suitable for textured surfaces), with good long life & is resistant to most cleaning agents. The coloured diagonal stripes highlight danger, hazard & safety areas. The 0011 can define & highlight potential hazards such as low headroom, obstructions like posts & racking.

Widths: Slit to customer requirements. max:1350 mm Colour: Yellow / Black Roll Length: 25 m

Reflective Hazard Tape 9650

High Reflectivity Identification Warning Tape. High Reflectivity for clear stand out identification of

hazard areas.

Excellent for warehouses, factories, construction sites & service areas.
Effective warning indicator colours for parking areas, safety equipment & potential danger identification.
Acrylic adhesive provides long life adhesion, with good UV, weather & chemical resistance.

Reflective Warning Tape 9651

High Reflectivity Identification Warning Tape.

High Reflectivity for clear stand out identification of hazard areas.

Excellent for warehouses, factories, construction sites & service areas.

Effective warning indicator colours for parking areas, safety equipment & potential danger identification.

Acrylic adhesive provides long life adhesion, with good UV, weather & chemical resistance.

Widths: Slit to customer requirements, max:1000 mm Colour: Yellow / Black Thickness: 0.14 mm Roll Length: 10 m Widths: Slit to customer requirements, max: 450 mm Colour: Red / White Thickness: 0.10 mm Roll Length: 10 m

