

FUTUREPROTECT
KRAFT MASKING PAPER

PRODUCT DATA SHEET

3914-02
3928-02
3943-02

DESCRIPTION

Kraft Masking Paper is an essential tool for professional painters and DIY enthusiasts. Designed to offer exceptional surface protection during painting projects, it serves as a barrier to overspray, drips, and spills while maintaining ease of application.

Whether for automotive, commercial, or residential use, this masking paper provides reliability and consistency, assisting with clean lines and a professional finish every time.



BENEFITS AND FEATURES



HIGH STRENGTH
High Strength with easy fold down to cover & protect.



VERSATILE APPLICATION
Suitable for a wide range of painting projects.



EXCELLENT MOISTURE RESISTANCE

TYPICAL APPLICATIONS

- Interior and exterior painting.
- Commercial and residential construction.
- Automotive refinishing.
- Spray paint protection.
- Commercial and residential construction.

KEY CHARACTERISTICS

- High Durability: Made from brown kraft paper, this product resists tears and punctures, providing effective coverage even in tough environments.
- Moisture Resistance: Non-absorbent kraft paper to hold paint but not leach through.
- Versatile Application: Suitable for a wide range of painting projects, including walls, trim, baseboards, and more. For interior and exterior applications.
- Easy Application: Available in various sizes, simplifying the masking process for any surface.

TECHNICAL INFORMATION

Property	Average
Basis Weight	50 gsm
Moisture	8.5 %
Color (b*)	21.82
Caliper	93.4 Microns
Machine Direction (MD) Tensile Strength	2.24 kN/m
Cross Direction (CD) Tensile Strength	1.04 kN/m
Cross Direction (CD) Tear Strength	253 mN
Burst Strength	58.4 kPa
Sheffield Roughness (Top)	142.1 SU
Sheffield Roughness (Wire)	142.3 SU
Cobb (1 min)	45 gsm
Available Sizes:	3914-02 (144mmx50m)
	3928-02 (288mmx50m)
	2943-02 (432mmx50m)

INSTRUCTIONS FOR USE

- **Surface Preparation:** Ensure the surface is clean and dry before applying masking paper.
- **Application:** Secure the kraft masking paper with masking tape, ensuring full coverage of areas you wish to protect.
- **Removal:** Once the painting project is complete, remove the masking paper gently to avoid damaging the painted surface.

NOTE: We recommend tape product testing to assess the suitability of the selected product to the end application & conditions. For surface preparation and guidelines please refer to our website www.tapespec.co.nz Advanced Tape Application Guide.

SURFACE SUBSTRATE CONDITION & PREPARATION

The surfaces to be bonded must be dry & free from any contamination including dust, oils, & fats, oxidation, release agents & any other known contamination.

The bond strength is dependent upon the contact pressure of the adhesive to substrate. To assist this process all adhesive tapes require firm hand or roller pressure.

BONDING APPLICATION TEMPERATURE

We recommend that the product, substrate & environment should be between -10°C ~ 50°C. Ensure that the adhesive product & substrates are allowed time to adjust to the environment temperature before bonding. For product storage we recommend that products are stored in their original packaging under dry conditions, ideally at room temperature but not warmer than +25°C. High relative humidity & direct sunlight must be avoided at all costs.

For more detailed handling instructions please refer to our comprehensive application guide.

PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose, prior to use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information please refer to our detailed Surface Condition & Preparation Guide.