

TAPESPEC WASHI RANGE

The Professional's Choice

ADHESION GUIDE

MEDIUM



DELICATE

EXTREME



1	2	G	6	S	14
Delicate Surface	Multi Surface	Light Textured Surface	Textured Surface	Rough Surface	Difficult Surface
ADHESION: LOW	ADHESION: LOW - MEDIUM	ADHESION: MEDIUM	ADHESION: MEDIUM - HIGH	ADHESION: HIGH	ADHESION: EXTRA HIGH
USED ON: <ul style="list-style-type: none"> Freshly painted surfaces (at least 24 hours' old) Vinyl coated wallpaper Primed wallboard Ceilings Cabinets Glass Excellent for various straight line striping, pattern, design applications Excellent for delicate curved profiles & irregular shapes / surfaces 	USED ON: <ul style="list-style-type: none"> Delicate multi surfaces Cured painted surfaces Ceilings Skirting boards Sealed woodwork & trim Glass & metal surfaces Sealants & silicone masking 	USED ON: <ul style="list-style-type: none"> Lightly textured woodwork, framework Ceilings Glass & metal surfaces Plastic 	USED ON: <ul style="list-style-type: none"> Excellent conformability for textured & rough surfaces Textured walls & woods Carpets Concrete, stucco & stone work Plastics Glass & metal surfaces Sealants & silicone masking 	USED ON: <ul style="list-style-type: none"> Slightly damp textured & uneven surfaces Excellent on cedar timber Non-flaky woodwork Most metal, glass & plastic surfaces Carpets Polished concrete, tiles & composite panels Sealants & silicone masking 	USED ON: <ul style="list-style-type: none"> Elastomeric paint & waterproof membrane paint systems Sandblasting & marine masking applications Concrete, stucco, tiles, composite panels & plastics Aluminium & metals Excellent for securing heavy duty plastic masking films
					Made from: Woven Plastic Film (LUPIN) . Up to 30 days exterior clean removal